



## China 608 Bearing Supplier

High Precision 32206 32207 32208 Stainless Steel  
Standard Tapered Roller Bearing Size High  
Precision Timken, NSK, SKF, FAG,

Bearing No. 32206

|                       |               |
|-----------------------|---------------|
| Category              | Bearings      |
| Inventory             | 0.0           |
| Manufacturer Name     | SKF           |
| Minimum Buy Quantity  | N/A           |
| UNSPSC                | 31171516      |
| Weight                | 0.275         |
| EAN                   | 7316570581751 |
| Product Group         | B04334        |
| Dimension series      | 3DC           |
| d                     | 30 mm         |
| D                     | 62 mm         |
| T                     | 21.25 mm      |
| d <sub>1</sub>        | 45.2 mm       |
| B                     | 20 mm         |
| C                     | 17 mm         |
| r <sub>1,2</sub> min. | 1 mm          |
| r <sub>3,4</sub> min. | 1 mm          |
| a                     | 15.144 mm     |
| d <sub>a</sub> max.   | 37 mm         |
| d <sub>b</sub> min.   | 37 mm         |
| D <sub>a</sub> min.   | 52 mm         |
| D <sub>a</sub> max.   | 56 mm         |
| D <sub>b</sub> min.   | 58 mm         |
| C <sub>a</sub> min.   | 3 mm          |
| C <sub>b</sub> min.   | 4 mm          |
| r <sub>a</sub> max.   | 1 mm          |



## China 608 Bearing Supplier

|                                |             |
|--------------------------------|-------------|
| $r_b$ max.                     | 1 mm        |
| Basic dynamic load rating C    | 61.8 kN     |
| Basic static load rating $C_0$ | 57 kN       |
| Fatigue load limit $P_u$       | 6.3 kN      |
| Reference speed                | 9000 r/min  |
| Limiting speed                 | 11000 r/min |
| Calculation factor e           | 0.37        |
| Calculation factor Y           | 1.6         |
| Calculation factor $Y_0$       | 0.9         |
| Mass bearing                   | 0.29 kg     |