



## China 608 Bearing Supplier



30207JR Bearing 2D drawings and 3D CAD models

Motorcycle Spare Parts KOYO 30207JR  
Bearings Best Selling Low Noise Tapered Roller  
Bearing Rodamiento 30207 Rolamento

Bearing No. 30207JR

Size	35x72x18.25 mm
Bore Diameter	35 mm
Outer Diameter	72 mm
Width	18,25 mm
d	35 mm
D	72 mm
T	18,25 mm
B	17 mm
C	15 mm
a	15,3 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	43,5 mm
da max	44 mm
Da min	62 mm
Da max.	63,5 mm
Db min.	67 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,344 Kg
Basic dynamic load rating (C)	55,1 kN
Basic static load rating (C0)	60,9 kN
(Grease) Lubrication Speed	5600 r/min
(Oil) Lubrication Speed	7400 r/min



## China 608 Bearing Supplier

Calculation factor (e)	0,37
Calculation factor (Y0)	0,88
Category	Tapered Roller Bearing Assemblies
Inventory	3.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.34
Product Group	B04334
Precision Class	Standard
Component	Assembly
Basic Number	30207
Number of Tapered Rows	Single Row
Inch - Metric	Metric
Other Features	High Load Capacity
Long Description	Assembly; Standard Precision; 35MM Bore; 72MM Outside Diameter; 18.25MM Assembly Width; Single Row of Rollers
Category	Tapered Roller Bearings Assembly
UNSPSC	31171516
Harmonized Tariff Code	8482.20.00.00
Noun	Bearing
Keyword String	Tapered
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Manufacturer Item Number	30207JR
Weight / LBS	0.758
Bore	1.378 Inch   35 Millimeter
Assembly Width	0.719 Inch   18.25 Millimeter
Outside Diameter	2.835 Inch   72 Millimeter
Flange Outside Diameter	0 Inch   0 Millimeter



## China 608 Bearing Supplier

Bearing No.	30207JR
r(min)	1.5
r1(min)	1.5
Cr	68.8
C0r	60.9
Cu	8.95
Grease lub.	5600
Oil lub.	7400
a	15.3 mm
da(min)	43.5
db(max)	44
Da(max)	63.5
Da(min)	62
Db(min)	67
Sa(min)	3
Sb(min)	3
ra(max)	1.5
rb(max)	1.5
e	0.37
Y1	1.60
Y0	0.88
(Refer.)Mass(kg)	0.344